



KAMCO LTD
SAFETY DATA SHEET
Systemsafe IC

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name: Systemsafe IC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: A liquid corrosion inhibitor.

1.3. Details of the supplier of the safety data sheet

Company Name: KAMCO LTD
Unit 9, Curo Park, Frogmore,
ST ALBANS, HERTS, AL2 2DD
Tel: 01727 875020, Fax: 01727 875335
Email: info@kamco.co.uk Website: www.kamco.co.uk

1.4. Emergency telephone number

01727 875 020 (Office Hours 8-5)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: T:R25; Xi:R36/38; Sens.:R43;

Classification under CLP: Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Toxic if swallowed. Irritating to eyes and skin. May cause sensitisation by skin contact.

2.2. Label elements

Label Elements under CLP:

Hazard statements: H302: Harmful if swallowed.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.

Signal word: Warning

Hazard pictograms:



Precautionary statements: P264: Wash skin thoroughly after handling.
P280: Wear <protective gloves/protective clothing/eye protection/face protection>.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
P321: Specific treatment (see ... on this label).
P330: Rinse mouth.

Label Elements under CHIP:

KAMCO LTD

SAFETY DATA SHEET

Systemsafe IC

Hazard Symbols:



Risk phrases: R25: Toxic if swallowed; R36/38: Irritating to eyes and skin; R43: May cause sensitisation by skin contact;

Safety phrases: S24: Avoid contact with skin; S37: Wear suitable gloves; S38: In case of insufficient ventilation, wear suitable respiratory equipment; S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label wher);

Precautionary phrases:

2.3. Other hazards

PBT: This substance is not identified as a PBT substance

Section 3: Composition/information on ingredients

3.2. Hazardous ingredients

Ingredients	EINECS	CAS	Reach Reg No.	CHIP Class	CLP Class	Percent
SODIUM NITRITE	231-555-9	7632-00-0	01-2119471836-27-XXXX	T:R25; N:R50; O:R8;	Ox. Sol. 3: H272; Acute Tox. 3: H301; Aquatic Acute 1: H400	10-30%
2-PHOSPHONOBUTANE-1,2,4-TRICARBOXYLIC ACID	253-733-5	37971-36-1	01-2119436643-39-XXXX	Xi:R36;	Eye Irrit. 2: H319; Met. Corr. 1: H290	1-10%
SODIUM HYDROXIDE	215-185-5	1310-73-2	01-2119457892-27	:R35;		<1%
A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-O		55965-84-9		:R34; T:R23/24/25; Sens.:R43; N:R50/53;	Acute Tox. 3: H301Acute Tox. 3: H311Acute Tox. 3: H331; Acute Tox. 3: H301Acute Tox. 3: H311Acute Tox. 3: H331; Acute Tox. 3: H301Acute Tox. 3: H311Acute Tox. 3: H331; Skin Corr. 1B: H314; Skin Sens. 1: H317;	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

KAMCO LTD

SAFETY DATA SHEET

Systemsafe IC

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and Storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Polyethylene. Unsuitable packaging: metals and alloys.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control Parameters

Ingredients	State	Workplace exposure limits		Respirable dust	
		8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
SODIUM HYDROXIDE	CS	1 mg/m3	2 mg/m3	-	-

KAMCO LTD

SAFETY DATA SHEET

Systemsafe IC

SODIUM HYDROXIDE	DA	2 mg/m3	2 mg/m3	-	-
SODIUM HYDROXIDE	FR	2 mg/m3		-	-
SODIUM HYDROXIDE	IR		2 mg/m3	-	-
SODIUM HYDROXIDE	UK	-	2 mg/m3	-	-
A MIXTURE OF: 5-CHLORO-2-METHY	UK	0.05 mg/m3	-	-	-

8.1. DNEL/PNEC Values

DNEL / PNEC: No data available

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid
 Solubility in water: Miscible in all proportions
 Colour: Pale yellow
 Relative density: 1.181 pH: 7.8-9
 Odour: Barely perceptible odour
 Viscosity:

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical Stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage condition

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Soft metals (aluminium, zinc etc.) Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

A MIXTURE OF: 5-CHLORO-2-METHY

ORL	RAT	LD50	53	mg/kg
ORL	MUS	LD50	60	mg/kg

SODIUM HYDROXIDE

ORL	RBT	LDLO	500	mg/kg
-----	-----	------	-----	-------

KAMCO LTD

SAFETY DATA SHEET

Systemsafe IC

IPR	MUS	LD50	40	mg/kg
-----	-----	------	----	-------

SODIUM NITRITE

SCU	RAT	LD50	96600	µg/kg
ORL	RAT	LD50	180	mg/kg
ORL	MUS	LD50	175	mg/kg

Effects of mixture

Calculated

11.2. Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.
Exposure may cause coughing or wheezing.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility in solid: Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Return empty containers to the supplier for recycling. Damaged containers should be destroyed by cutting up or by incineration. Do not use for potable water.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN Number

UN number: 3287

14.2. UN Proper shipping name

Shipping name: TOXIC LIQUID, INORGANIC, N.O.S.(SODIUM NITRITE)

14.3. Transport hazard class(es)

Transport class: 6.1

KAMCO LTD

SAFETY DATA SHEET

Systemsafe IC

14.4. Packing Group

Packing group: III

14.6. Special precautions for user

Tunnel Code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier as use on site is variable. Risk assessment is supplemented by a site specific COSHH sheet.

Section 16: Other information

Chemical safety assessment: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010

Phrases used in s.2 and 3:

- H272: May intensify fire; oxidiser.
- H290: May be corrosive to metals.
- H301: Toxic if swallowed.
- H302: Harmful if swallowed.
- H311: Toxic in contact with skin.
- H314: Causes severe skin burns and eye damage.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H319: Causes serious eye irritation.
- H331: Toxic if inhaled.
- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.
- R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.
- R25: Toxic if swallowed.
- R34: Causes burns.
- R35: Causes severe burns.
- R36/38: Irritating to eyes and skin.
- R36: Irritating to eyes.
- R43: May cause sensitisation by skin contact.
- R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- R50: Very toxic to aquatic organisms.
- R8: Contact with combustible material may cause fire.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.